

AXIS M5013 PTZ Dome Network Camera

Mini PTZ dome that gives the big picture

AXIS M5013 is an ultra-discreet, palm-sized, pan/tilt/zoom camera for remote indoor monitoring. The ceiling-mount camera enables flexible coverage over a 400 m² (4300 sq. ft) area, with a $\pm 180^\circ$ pan, 90° tilt and 3x digital zoom. It provides full frame rate video in SVGA resolution. It supports multiple H.264 and Motion JPEG video streams. The IP51 rating ensures protection against dust and dripping water, enabling the camera to operate even when a sprinkler system is activated. With a built-in microphone, AXIS M5013 enables users to listen to and record audio remotely. It also supports audio detection.

- > [Pan, tilt, zoom in an ultra-discreet design](#)
- > [SVGA and H.264](#)
- > [IP51-rated protection against dust and dripping water](#)
- > [Power over Ethernet \(IEEE 802.3af\)](#)
- > [Built-in microphone and audio detection](#)



AXIS M5013 PTZ Dome Network Camera

Camera	
Image sensor	Progressive scan RGB CMOS 1/4"
Lens	3.6 mm, F1.8 Horizontal field of view: 45° Vertical field of view: 32°
Minimum illumination	1.4 lux, F1.8
Shutter time	1/25000 s to 1/6 s
Pan/Tilt/Zoom	25 preset positions Pan: ±180°, 100°/s Tilt: 90°, 100°/s Zoom: 3x digital zoom
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG
Resolutions	800x600 SVGA to 320x180
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/MBR H.264
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Rotation, Backlight compensation, Fine tuning of behavior at low light, Text overlay
Audio	
Audio streaming	One-way
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate
Audio input	Built-in microphone
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH
System integration	
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S
Analytics	Video motion detection, Audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line

	Detection, AXIS Digital Autotracking and third-party applications.
Event triggers	Analytics, PTZ preset, Memory card full
Event actions	File upload: FTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Go to PTZ preset; Video recording to edge storage Pre- and post-alarm video buffering
Built-in installation aids	Pixel counter
General	
Casing	IP51-rated plastic casing, clear dome
Sustainability	PVC free
Memory	256 MB RAM, 128 MB Flash
Power	Power over Ethernet 802.3af/802.3at Type 1 Class 3
Connectors	RJ45 10BASE-T/100BASE-TX PoE
Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EN 55022 Class A, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class A, VCCI Class B, RCM AS/NZS CISPR 22, KCC KN22 Class A, KN24, EN 60950-1 IEC/EN 60529 IP51
Dimensions	Ø130 x 58 mm (Ø5 1/8 x 2 1/4 in)
Weight	330 g (0.7 lb)
Included accessories	Drill template, Installation Guide, Windows decoder 1-user license AXIS M50 Clear Dome AXIS M50 Mounting Kit
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option