

AXIS P3915-R Network Camera

High-performance camera with audio for onboard surveillance

AXIS P3915-R is specially designed for HDTV 1080p video surveillance in or on vehicles. The compact, rugged and discreet camera has IP67-rated protection against dust and water, and can withstand tough conditions such as vibrations, shocks and temperature fluctuations. The active tampering alarm detects tampering attempts, such as blocking or spray-painting. AXIS P3915-R is specially adapted to respond quickly to changes in light levels, ensuring that high image quality is maintained. Traffic Light mode helps distinguishing colors of traffic lights in very dark scenes. The pixel counter helps verifying that the pixel resolution of an object meets specific customer requirements. AXIS P3915-R has audio-in and I/O capabilities.

- > **Compact, rugged design**
- > **HDTV video quality**
- > **Traffic Light mode**
- > **Audio-in**
- > **I/O ports**



AXIS P3915-R Network Camera

Models	AXIS P3915-R: RJ45 AXIS P3915-R: M12	PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP	
Camera			
Image sensor	1/2.8" Progressive scan RGB CMOS	Data streaming Event data	
Lens	3.6 mm, F2.0, Horizontal field of view: 87° Vertical field of view: 47° M12 mount, fixed iris	Built-in installation aids Pixel counter	
Minimum illumination	Color: 0.2 lux	General	
Shutter time	1/28000 s to 2 s with 50 Hz 1/33500 s to 2 s with 60 Hz	Casing Aluminum and polycarbonate casing	
Camera angle adjustment	Pan: ±30° Tilt: 15-90° Rotation: ±175°	Sustainability PVC free	
Video			
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Memory 256 MB RAM, 128 MB Flash	
Resolutions	1920x1080 to 160x90	Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2, max. 4.3 W	
Frame rate	Up to 30 fps in all resolutions	Connectors RJ45: Male RJ45 10BASE-T/100BASE-TX M12: Rugged, Female, D-coded M12 connector with rotatable coupling nut All connectors support Power over Ethernet 3.5 mm Audio In connector, Mono, I/O 4-pin, 1 input, 1 output + 12 V DC/15 mA	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/MBR H.264	Storage Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations	
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Wide Dynamic Range-dynamic contrast, Backlight compensation, Fine tuning of behavior at low light, Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy mask, Mirroring of images, Traffic Light mode	Operating conditions -30°C to 60°C (-22°F to 140°F) Humidity: 10% - 95% RH (non-condensing)	
Pan/Tilt/Zoom	Digital PTZ, Preset Positions, Guard Tour, Control Queue	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)	
Audio			
Audio streaming	Audio in, Simplex	Approvals EMC EN 55022 Class B, EN 55024, EN 50581, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24 Safety IEC/EN/UL 60950-1 Environment IEC 60529 IP67, NEMA 250 Type 4X, IEC/EN 62262 IK08, EN 50155 Class T3, EN 45545, EN 50498, EN 50121-4, IEC 62236-4, ECE R10 rev.04 (E approval)	
Audio compression	AAC- LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Dimensions Height: 49 mm (1 15/16 in) ø 109 mm (4 3/16 in)	
Audio input	External microphone input or line input	Weight RJ45: 285 g (0.63 lb) M12: 293 g (0.65 lb)	
Network			
Security	Password protection, IP address filtering, HTTPS ^a encryption, network access control, Digest authentication, User access log, Centralized Certificate Management	Included accessories Installation guide, Windows decoder 1-user license, Drill hole template, Top cover tool, Lens tool, Allen key Resistorx [®]	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Optional accessories Lenses 6 mm, F1.6: Horizontal field of view: 52° 8 mm, F1.6: Horizontal field of view: 40° AXIS T96B05 External Housing, AXIS T94D01S Mounting Bracket, AXIS T94D02S Mounting Bracket, Network Coupler IP66, Network Cable Coupler Indoor For more accessories,	
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profiles S and G	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available.	
Analytics	AXIS Video Motion Detection 3, Active tampering alarm, Audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, Audio detection	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Event triggers	Analytics, Time scheduled, Edge storage events Audio Level, External input	Warranty Axis 3-year warranty and AXIS Extended Warranty option	
Event actions	Overlay text, video recording to edge storage, pre- and post-alarm video buffering, external output activation, send SNMP trap		