

AXIS P3364-VE Network Camera

Light-sensitive and vandal-resistant with remote focus and zoom

AXIS P3364-VE is a day and night fixed dome network camera that offers superb video performance in HDTV 720p/1 MP resolution. It provides multiple, individually configurable H.264 and Motion JPEG video streams. Digital pan/tilt/zoom allows a view cropped from the full view to be streamed for viewing or recording. P-iris control provides optimal depth of field, resolution, image contrast and clarity. Remote zoom and focus eliminate the need for hands-on fine tuning. AXIS P3364-VE supports Axis' Lightfinder technology, making it extremely sensitive to low light. With its weather-proof and vandal-resistant casing, it is perfectly adapted for harsh environments. Its operating temperature ranges from -40 °C to 55 °C (-40 °F to 131 °F).

- > [HDTV 720p/1 MP](#)
- > [Lightfinder technology](#)
- > [P-Iris control](#)
- > [Remote focus and zoom](#)
- > [Outdoor-ready and vandal-resistant design](#)



AXIS P3364-VE Network Camera

Models	AXIS P3364-VE 6 mm AXIS P3364-VE 12 mm	Event triggers	Analytics, Edge storage events External input
Camera		Event actions	File upload: FTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Video recording to edge storage Pre- and post-alarm video buffering External output activation, Audio recording to edge storage, Play audio clip
Image sensor	Progressive scan RGB CMOS 1/3"	Data streaming	Event data
Lens	6 mm: 2.5–6 mm, F1.2 Horizontal angle of view: 105°–49° Vertical angle of view: 80°–37° 12 mm: 3.3–12 mm, F1.4 Horizontal angle of view: 82°–24° Vertical angle of view: 60°–18° Varifocal, Remote focus and zoom, P-Iris control, IR corrected	Built-in installation aids	Remote zoom, Remote focus, Pixel counter
Day and night	Automatically removable infrared-cut filter	General	
Minimum illumination	6 mm: Color: 0.12 lux, F1.2, B/W: 0.03 lux, F1.2 12 mm: Color: 0.18 lux, F1.4, B/W: 0.04 lux, F1.4	Casing	Polycarbonate transparent dome, aluminum inner camera module with encapsulated electronics IP66- and NEMA 4X-rated, IK10 impact-resistant casing with aluminum base and dehumidifying membrane Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner.
Shutter time	1/24500 s to 2 s	Memory	256 MB RAM, 128 MB Flash
Camera angle adjustment	Pan 360°, Tilt 170°, Rotation 340°	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 12.1 W
Video		Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 alarm input and 1 output, 3.5 mm mic/line in, 3.5 mm line out
Video compression	H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC), Motion JPEG	Edge storage	Support for SD/SDHC/SDXC card Support for recording to dedicated network-attached storage (NAS)
Resolutions	1280x960 ^a (approx. 1.3 MP) to 160x90	Operating conditions	-40 °C to 55 °C (-40 °F to 131 °F) Humidity 10-100% RH (condensing)
Frame rate	25/30 fps with power line frequency 50/60 Hz	Approvals	EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78, EN 50121-4, IEC 62236-4, IEC/EN/UL 60950-22, IEC 62262 IK10, IEC/EN 60529 IP66, NEMA 250 Type 4X
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264	Dimensions	Ø178 x 119 mm (Ø7 x 4 11/16 in)
Pan/Tilt/Zoom	Digital PTZ	Weight	1.5 kg (3.3 lb) with weather shield
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, Mirroring of images, Privacy mask, Wide Dynamic Range - Dynamic Contrast Rotation 0°, 90°, 180°, 270°, including Corridor Format	Included accessories	Installation Guide, Windows decoder 1-user license, Resistorx T20 screw driver, Drill hole template Connector kit, Mounting bracket, 5 m (16 ft) network cable with pre-mounted gasket Weather shield, Smoked dome
Audio		Optional accessories	AXIS P33 Series Pendant Kit AXIS T8120 Midspan 15 W 1-port AXIS T8415 Wireless Installation Tool AXIS T94H01P Conduit Back Box
Audio streaming	Two-way audio	Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development
Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Configurable bit rate	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
Audio input/output	External microphone input or line input, Line output	Warranty	Axis 3-year warranty and AXIS Extended Warranty option
Network			
Security	Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1X ^b network access control, Digest authentication, User access log		
Supported protocols	IPv4/v6, HTTP, HTTPS ^b , SSL/TLS ^b , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S,		
Analytics	Video motion detection, Active tampering alarm, Audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications,		